



**SUPPLEMENTAL/BID BULLETIN**  
**ADDENDUM NO. 19-006 (Goods)**

This Addendum No. **19-006 (Goods)** is issued to modify or amend items in the Bid Documents – with Solicitation No. 2019-01-008 which was posted in the PHILGEPSS with Reference No. 5938167. This shall form an integral part of the Bid Documents.

Name of Project : Procurement for the Supply and Delivery of WATERBATH, AUTOCLAVE AND BACTERIOLOGICAL INCUBATOR  
 EMB-NCB-GOODS-08-2019

**INVITATION TO BID (page 4):**

Old	New
5. A complete set of Bidding Documents may be acquired by interested Bidders on <b>December 28, 2018 to January 18, 2019, 8:00 a.m. to 2:00 p.m.</b> from the address below and upon payment of a nonrefundable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, in the amount of <b>Php5,000.00</b> .	5. A complete set of Bidding Documents may be acquired by interested Bidders on <b>December 28, 2018 to January 18, 2019, 8:00 a.m. to 2:00 p.m.</b> from the address below and upon payment of a nonrefundable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, in the amount of <b>Php1,000.00</b> .

**TECHNICAL SPECIFICATIONS (page 68):**

Old	New
<b>Waterbath</b> -min. 5°C above ambient up to +95°C with additional boiling mode (+100°C) -corrosion-proof large-area heating on three sides -digital display (LED) -easy-to-clean interior, made of stainless steel, reinforced by deep drawn ribbing, -humidity: max. 80 %, non-condensing -220V, 50/60 Hz -overtemperature protection -volume: 45 L inclusion: 1 unit AVR (3000 watts)	<b>Waterbath</b> -min. 5°C above ambient up to +95°C with additional boiling mode (+100°C) -corrosion-proof large-area heating on three sides -digital display (LED) -easy-to-clean interior, made of stainless steel, reinforced by deep drawn ribbing, -humidity: max. 80 %, non-condensing -220V, 50/60 Hz -overtemperature protection -volume: 45 L inclusion: 1 unit AVR (3000 watts)  <b>Additional specifications:</b> -with gable cover
<b>Autoclave</b> -working temperature: 110 to 135°C -working pressure: 3 to 30 psi -sterilization timer -capacity: ≥50L -door closure sensor -lid sensor -programmable auto start -pressure overload protection -overheat & over pressure protection	<b>Autoclave</b> -working temperature: 110 to 135°C -working pressure: 3 to 30 psi -sterilization timer -capacity: ≥50L -door closure sensor -lid sensor -programmable auto start -pressure overload protection -overheat & over pressure protection

<p>-power supply: 220/230V, 50/60 Hz          -pressure relief valve          -includes stainless steel mesh wire basket          -includes stainless steel test tube racks</p>	<p>-power supply: 220/230V, 50/60 Hz          -pressure relief valve          -includes stainless steel mesh wire basket  <b>-includes stainless steel/autoclavable plastic test tube racks (4 pieces, 24 holes fit for 25mm test tubes)</b></p>
<p>Note: suppliers must be exclusive distributor</p>	<p>Note: suppliers must have a certificate of distributorship with aftersales</p>

For guidance and information of all concerned.

  
 ENGR. MA. CORAZON G. DACUYAN  
 BAC Chairperson

Received by the Bidder:

\_\_\_\_\_

Date: \_\_\_\_\_